

GRIZZLY 700



The GRIZZLY 700 goes into high gear with a new 708cc powerful engine and a higher torque. Its new compact bodypart is equipped with LED lights and a halogen work light.



Colors
available



MOTOR

Maximum power (Kw / rpm)	
Engine type	Single cylinder, 4-stroke, DOHC, 4-valves
Displacement (cc)	708
Cooling system	Liquid-cooled
Compression ratio	10,1 : 1
Maximum power (hp / rpm)	NC
Maximum torque (N.m / rpm)	NC
Starter system	Electric starter
Lubrication system	Wet sump
Ignition system	TCI
Fuel delivery	Mikuni electronic injection



CHASSIS

Frame	NC
Front suspension system	Independent double wishbone, 193 mm wheel travel
Rear suspension system	Independent double wishbone, 232 mm wheel travel
Front brake	Dual ventilated hydraulic disk
Rear brake	Left foot or right hand operation
Wheels	Aluminum
Front tyre	Maxxis MU19 AT26x8-12 acier
Rear tyre	Maxxis MU19 AT26x10-12 acier



DIMENSIONS

Overall dim - L x w x h (mm)	2070*1230*1253
Wheelbase (mm)	1253
Seat height (mm)	860
Min ground clearance (mm)	288



TRANSMISSION

Transmission system	Automatic (CVT)
----------------------------	-----------------



WEIGHT/CAPACITIES

Dry weight (kg)	290
Fuel tank capacity (L)	18



EQUIPMENT



Luggage rack



Electric starter



Disc brake



Power steering



Diff-lock

THE
rules

2

1 Always wear a helmet, eye protection and protective proper clothing.

2 YAMAHA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

For more information, please contact your dealer YAMAHA.

