

DT125



Its maintenance simplicity does the difference because no ground conditions can terrify the 2-stroke engine and the monocross suspension of the DT125. Easy to repair, and cheap to maintain, this is one of the references of the governments, NGOs, and companies.



Colors
available



MOTOR

Engine type	Single cylinder, 2-stroke
Displacement (cc)	125
Cooling system	Air-cooled
Compression ratio	7,2 : 1
Maximum power (hp / rpm)	15 / 7000
Maximum torque (N.m / rpm)	15,2 / 6500
Starter system	Kick starter
Lubrication system	Autolube
Ignition system	CDI
Fuel delivery	Carburetor



CHASSIS

Frame	Double steel cradle
Front suspension system	Telescopic fork
Rear suspension system	Swingarm (monocross)
Front brake	Drum
Rear brake	Drum
Wheels	Spoke
Front tyre	2,75-21 4PR
Rear tyre	4,10-18 4PR



DIMENSIONS

Overall dim - L x w x h (mm)	2110*865*1165
Wheelbase (mm)	1340
Seat height (mm)	830
Min ground clearance (mm)	260



TRANSMISSION

Transmission system	6-speed
---------------------	---------



WEIGHT/CAPACITIES

Dry weight (kg)	98
Fuel tank capacity (L)	9,50



EQUIPMENTS



Luggage
Pack

Kick
starter

Spoke
wheels

THE 2 rules

1 Always wear a helmet, eye protection and protective proper clothing.

For more information, please contact your dealer YAMAHA.

2 YAMAHA encourages you to ride safely with responsible manners that comply with all laws while respecting the environment.

